

TYPICAL SPECIFICATIONS

V25

Typical properties

APPEARANCE	VISCOUS LIQUID
COLOR	BROWN
Flash Point (ASTM D 93)	156°C
POUR POINT (ASTM D 97)	< -33°C
SPECIFIC GRAVITY	0.91 g/ml
Viscosity 20°C (ASTM D445)	539 cSt
pH	6.5
SOLUBILITY IN	
PETROLEUM PRODUCTS	SOLUBLE
WATER	INSOLUBLE

Description

ADERCO V25 is a multi-functional additive specially formulated to:

- homogenize the fuel
- eliminate water
- increase diesel fuel lubricity
- optimize atomization
- improve combustion
- reduce smoke
- maintain optimum performance
- reduce diesel fuel consumption
- minimize pollution

Dosage

The normal dosage of **Aderco V25** is 1 liter for 10,000 liters of fuel. If required, the dosage can be raised up to 1 liter for 1,000 liters of fuel without problems.

Blending

Simply add the required quantity of **ADERCO V25** to the diesel tank before fuelling. The movements of the vehicle will be sufficient to adequately mix the additive.

Freight classification

UN Number: NOT APPLICABLE

Not regulated for transport

Shipping

Available in 200 liter non-returnable steel drums and in 20 liter plastic pails.

	200 lts	20 lts
Net	182 kg	18.2 kg
Gross	202 kg	19.4 kg

Customs classification

Harmonized Tariff System: 3811.90

Handling

Normal precautions for handling petroleum products should be observed:

- **If skin contact does occur:** wash affected areas with soap and water.
- **If eye contact does occur:** immediately wash with copious amounts of clean water or an eye-wash solution for at least 10 minutes.

Storage

ADERCO Fuel Oil Treatments are chemically very stable and will remain in storage for prolonged periods under extreme temperature conditions without undergoing any chemical alteration.

